



Sơn Nippon  
Sơn Dầu Cũng Đẹp

Ref. No. : PDS-0116-EN

Version No. : 3

Revision Date : 17.12.18

## PRODUCT DATA SHEET

### WEATHERGARD SKIMCOAT\*\*

<b>Description</b>	Nippon Paint WEATHERGARD SKIMCOAT** is specially formulated to meet your need for patching of hairline cracks and smoothening of walls to enhance the aesthetics of masonry surfaces.
<b>Uses</b>	Nippon WEATHERGARD SKIMCOAT** is used as a putty for exterior substrates such as: - Cement plasters                      - Concrete                      - Brickworks
<b>Finish</b>	Matt/ White
<b>Features</b>	<ul style="list-style-type: none"> <li>- Very tough and durable</li> <li>- Excellent adhesion of recommended substrates</li> <li>- No cracking tendency under normal application</li> <li>- Better water resistance</li> <li>- Easier to sand</li> </ul>
<b>APPLICATION DATA</b>	
<b>Surface Preparation</b>	Ensure the surface is clean and stable. Extremely dry and absorbent substrates should be moistened with water before applying WEATHERGARD SKIMCOAT**.
<b>Application Methods</b>	Use trowel to apply WEATHERGARD SKIMCOAT** on the surface with thickness of 1 mm depend on the surface. Wait for 16 hours or until the surface is partially settled then apply a second coat of similar thickness. Sanding the surface to give a smooth finish.
<b>Paint Consumption</b>	Theoretical: 30 - 40 m <sup>2</sup> /bag (40Kg) depend on thickness applied
<b>Mixing Instruction</b>	Mix 01 bag WEATHERGARD SKIMCOAT** with 15 - 17 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes). Add powder to water to avoid lumpiness. Allow the mixture to stand for about 10 minutes then mix again until homogenous. Ready plaster should be used in 2 hours after mixing.
<b>Cleaning</b>	Wash all equipment immediately after use with clean water
<b>Storage</b>	WEATHERGARD SKIMCOAT** is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.

## NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

[www.nipponpaint.com](http://www.nipponpaint.com)

## WEATHERGARD SKIMCOAT\*\*

<b>Packing</b>	40 Kgs/Bag
<b>Precaution</b>	<p>Do not use WEATHERGARD SKIMCOAT** on unstable painted surfaces, water soluble plasters or smoothing floors.</p> <p>Do not apply WEATHERGARD SKIMCOAT** when the temperature is below 10°C &amp; moisture is over 85%.</p>
<b>NOTE</b>	<p><i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales &amp; Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i></p>

### NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

[www.nipponpaint.com](http://www.nipponpaint.com)